## Reliable power in a compact 1 tractable body



Heavy-duty rear suspension

235mm of ground clearance

Ill pendable front and rear drum brakes

## **EATURES**

Reliable 2-stroke air-cooled single 97cc engine features Yamaha-original 7-port"Torque Induction"system for added scavenging efficiency.

Virtually maintenance-free CDI system supplies a hot strong spark at all times.

 Positive shifting 5-speed transmission allows the rider to make the best of the delivered power over the entire speed range.

Heavy-duty rear suspension is adjustable to surface and load conditions, smoothening out the roughest terrain.

Dependable front and rear drum brakes are water-and-dust resissant in all terrain conditions.

· 235mm of ground clearance is enough for safe, smooth operation in the toughest terrain.

Mudproof footrests are effective to increase both convenience and comfort for the in muddy surface conditions.

Front and rear knobby tyres provide better surface grip.

## **PECIFICATIONS**

ENGINE	2 steeles single
Type	2-stroke, single
Bore & stroke	.52.0 × 45.0 mm
Compression ratio	
	age, 250 rpm
Max. torque (DIN)1.05	#g-m (10.3 Nm)
Lubrication	Autolube
Carlurgition	TARREST VINLAN
Ignition	MARKET STREET
Fool bank canacity	AND DESCRIPTION OF THE PARTY OF
Oil caracity	A STATE OF THE PARTY OF THE PAR
Transmission Final transmission	Chain drive

CHASSIS	,
Overall length	2.110 mm
Overall width	
Overall height	1,080 mm
Seat height	500 mm
Wheelbase	
Ground clearance .	mm Z35 mm
Dry weight	
Suspension (Front)	Telescopic forks
(Reur)	Swingarm
Brakes (Front)	awarana ana ana ana ana ana ana ana
(Rear) .	Drum
Tyres (Front)	2.75-19-4PR
(Rear)	3.50-18-4PR

www.legends-yamaha-enduros.com