Increased total performance in competition



E-section rims

Front brake lining wear indicator

FEATURES

- 2-stroke single 311cc reed-catte engine gives an amazingly stable low-end torque for instant response to the most delicate throttle operation.
- * 6-speed transmission has four close ratio bottom years and two wider ratios above.
- Front brake lining ucar indicator allows quick, visual checking
- . Sturdy 36 mm forks provide 180 mm of wheel travel.
- Monocross suspension system features a rising-rate linkage and a De Carbon type shock absorber.
- E-section rims are fitted with ultra-soft, high-grip trials types.
- Diamond-pattern type frame uses the engine as a stressed member for maximum rigidity.
- Speedometer and odometer are standard
 construent

www.legends-yamaha-enduros.com

SPECIFICATIONS

ENGINE
Type2-stroke, sing
Displacement341
Bore & stroke
Compression ratio
Max. power (DIN) 21.5 PS (15.8 kV
@5,000 rps
Max. torque (DIN) 3.4 kg-m (33.8 Nn
@2,500 rps
LubricationPre-mi
Carburetion
Ignition
Starter system
Fuel tank capacity
Transmission
Final transmission Chain drive
CHASSIS
Overall length
Overall width805 mn
Overall height 1,085 mn
Seat height
Wheelbase
Ground clearance
Dry weight
Suspension (Front) Telescopic forks
(Rear)Monocross suspension
Brakes (Front)
(Rear)
Tyres (Front)2.75-21-4PR