A dependable, versatile workhorse Rugged front and rear carriers Mudproof footrests Proven 2-stroke air-cooled single 171cc engine Special front and rear flaps Front and rear knobby tyres Heavy-duty rear suspension

G175

FATURES

- Proven 2-stroke air-cooled single engine with Yamaha original 7-port Torque Induction system ensures better scavenging effect for more power.
- Mudproof footrests help increase both contenience and comfort for the rider while negotiating muddy surface conditions.
- Heavy duly rear suspension is adjustable to surface and wad condition, smoothering out the roughest terrain.

 Rusped front and rear carriers are
- Rugged front and rear carriers are standard equipment for added convenience in work or fun use.

- Front and rear knobby tyres provides better

 surface grip.
- * Special front and rear flaps also keep mud or Debbles from the rider.
- Smooth shifting 5-speed transmission lets the rider make full use of all the power from ultra low speed to full throttle.
- Virtually maintenance free CDI system
 provides a hot spark at all times.

S PECIFICATIONS

- I CONTIONIO	
ENGINE	Alberta sinala
Type	2-stroke, single
Displacement	and a second second second second
Bore & stroke	66.0 × 50.0 mm
Compression ratio	6.0:1
Max. power (DIN)	14.7 PS (10.9 kW)
Max. power (DIN)	#6,500 rpm
-0.440	1 20 hr - 116 0 hm
Max. torque (DIN)	1.72 sg-m (10.9 cvm)
	EESTSOO CALL
Lubrication	Autolube
Starter system	Kick .
Fuel tank capacity	11.0 /
Fuel tank capacity	1.5 /
Oil capacity	Sanand
Transmission	
Plant transmission	Chain onte

CHASSIS

Overall length 2,120 mm
Overall width 930 mm
Overall height
Seat height 805 mm
Wheelbase
Wheelbase 240 mm
Ground clearance 240 mm
Dry weight 106 kg
Suspension (Front) Telescopic forks
(Rear)Swingarm
Brakes (Front)
Tyres (Front) 3.00-19-4PR

www.legends-yamaha-enduros.com