



80 YAMIAHA

4-stroke Street



XS Eleven LG



XS850SG



XS400SG



XS Eleven SG



XS850G



SR250G

2-stroke Street



XS Eleven G



XJ650G



RD400G

4-stroke Enduro



XS850LG



XS650SG



XT500G

When you know how they're built, you'll buy a Yamaha.



XT250G

2-stroke Enduro



DT175G



DT125G



DT100G



DT50G



GT80G

4-stroke Off Road



TT250G

2-stroke Off Road



MX175G



MX100G



MX80G

International Trials



IT250G



IT175G

www.legends-yamaha-motors.com



IT125G

MX-machine



YZ465G



YZ250G



YZ125G



YZ100G



YZ80G



YZ50G



Soft Bike

QT50G



LC50G

TRI-moto 125



YT125G

SPECIFICATIONS

	XS Eleven LG	XS Eleven SG	XS Eleven G	XS850LG	XS850SG	XS850G	XJ650G	XS650SG
ENGINE								
Type	4-stroke D.O.H.C. four	4-stroke D.O.H.C. four	4-stroke D.O.H.C. four	4-stroke D.O.H.C. triple	4-stroke D.O.H.C. triple	4-stroke D.O.H.C. triple	4-stroke D.O.H.C. four	4-stroke S.O.H.C. twin
Displacement	1,101 cc	1,101 cc	1,101 cc	826 cc	826 cc	826 cc	653 cc	653 cc
Bore and Stroke	71.5 x 68.6 mm	71.5 x 68.6 mm	71.5 x 68.6 mm	71.5 x 68.6 mm	71.5 x 68.6 mm	71.5 x 68.6 mm	63 x 52.4 mm	75 x 74 mm
Compression ratio	9.0 : 1	9.0 : 1	9.0 : 1	9.2 : 1	9.2 : 1	9.2 : 1	9.5 : 1	8.7 : 1
Maximum torque	66.6 ft.-lbs. (9.2 kg-m) @ 6,500 r.p.m.	66.6 ft.-lbs. (9.2 kg-m) @ 6,500 r.p.m.	66.6 ft.-lbs. (9.2 kg-m) @ 6,500 r.p.m.	49.2 ft.-lbs. (6.8 kg-m) @ 6,500 r.p.m.	49.2 ft.-lbs. (6.8 kg-m) @ 6,500 r.p.m.	49.2 ft.-lbs. (6.8 kg-m) @ 6,500 r.p.m.	38.3 ft.-lbs. (5.3 kg-m) @ 7,500 rpm	39.8 ft.-lbs. (5.5 kg-m) @ 5,500 r.p.m.
Carburetion	(4) Mikuni BS34-II	(4) Mikuni BS34-III	(4) Mikuni BS34-III	(3) Hitachi HSC34	(3) Hitachi HSC34	(3) Hitachi HSC34	(1) Hitachi HSC32	(2) Mikuni BS34
Ignition	Transistor Controlled	Transistor Controlled	Transistor Controlled	Transistor Controlled	Transistor Controlled	Transistor Controlled	Transistor Controlled	Transistor Controlled
Starting	Electric	Electric	Electric	Electric & Kick	Electric & Kick	Electric & Kick	Electric	Electric & Kick
Lubrication	Wet sump	Wet sump	Wet sump	Wet sump	Wet sump	Wet sump	Wet sump	Wet sump
Transmission	5-speed/shaft drive	5-speed/shaft drive	5-speed/shaft drive	5-speed/shaft drive	5-speed/shaft drive	5-speed/shaft drive	5-speed/shaft drive	5-speed
CHASSIS								
Overall length	89.6" (2,275 mm)	89.6" (2,275 mm)	89.0" (2,260 mm)	86.6" (2,200 mm)	86.6" (2,200 mm)	85.6" (2,175 mm)	84.6" (2,150 mm)	83.9" (2,130 mm)
Overall width	33.7" (855 mm)	33.7" (855 mm)	36.2" (920 mm)	36.4" (925 mm)	36.4" (925 mm)	35.4" (900 mm)	33.9" (860 mm)	36.6" (930 mm)
Overall height	48.4" (1,230 mm)	48.4" (1,230 mm)	46.2" (1,175 mm)	49.8" (1,265 mm)	49.6" (1,265 mm)	46.9" (1,190 mm)	46.9" (1,190 mm)	48.2" (1,225 mm)
Seat height	31.1" (790 mm)	31.1" (790 mm)	31.5" (800 mm)	31.5" (800 mm)	31.5" (800 mm)	32.1" (815 mm)	29.5" (750 mm)	30.9" (787 mm)
Wheelbase	60.8" (1,545 mm)	60.8" (1,545 mm)	60.8" (1,545 mm)	58.7" (1,490 mm)	58.7" (1,490 mm)	57.1" (1,450 mm)	56.9" (1,445 mm)	56.5" (1,435 mm)
Ground clearance	6.1" (155 mm)	6.1" (155 mm)	5.9" (150 mm)	5.9" (150 mm)	5.9" (150 mm)	5.5" (140 mm)	5.9" (150 mm)	5.3" (135 mm)
Dry weight	556 lbs. (252 kg)	556 lbs. (252 kg)	562 lbs. (255 kg)	523 lbs. (237 kg)	523 lbs. (237 kg)	531 lbs. (241 kg)	441 lbs. (200 kg)	461 lbs. (209 kg)
Fuel tank capacity	3.3 Imp.gals. (15 ℓ)	3.3 Imp.gals. (15 ℓ)	4.4 Imp.gals. (20 ℓ)	3.7 Imp.gals. (17 ℓ)	3.7 Imp.gals. (17 ℓ)	3.7 Imp.gals. (17 ℓ)	2.9 Imp.gals. (13 ℓ)	2.5 Imp.gals. (11.5 ℓ)
Oil capacity	3.6 Imp.qts. (4 ℓ)	3.6 Imp.qts. (4 ℓ)	3.5 Imp.qts. (4 ℓ)	3.3 Imp.qts. (3.7 ℓ)	3.3 Imp.qts. (3.7 ℓ)	3.3 Imp.qts. (3.7 ℓ)	3.1 Imp.gals. (3.5 ℓ)	2.2 Imp.qts. (2.5 ℓ)
Suspension								
Front	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks
Rear	Swing arm	Swing arm	Swing arm	Swing arm	Swing arm	Swing arm	Swing arm	Swing arm
Brakes								
Front	Hydraulic discs (2)	Hydraulic discs (2)	Hydraulic discs (2)	Hydraulic discs (2)	Hydraulic discs (2)	Hydraulic discs (2)	Hydraulic disc (1)	Hydraulic disc (1)
Rear	Hydraulic disc (1)	Hydraulic disc (1)	Hydraulic disc (1)	Hydraulic disc (1)	Hydraulic disc (1)	Hydraulic disc (1)	Drum	Hydraulic disc (1)
Tires								
Front	3.50 H x 19	3.50 H x 19	3.50H x 19	3.25H x 19	3.25H x 19	3.25H x 19	3.25H x 19	3.50S x 19
Rear	130/90 x 16-67 H	130/90 x 16-67H	4.50H x 17	130/90 x 16-67H	130/90 x 16	130/90 x 17	130/90 x 16	130/90S x 16
Coloring	New Yamaha Black	New Ruby Red Black Red	Diamond Silver	New Yamaha Black	Black Blue New Ruby Red	New Yamaha Black	New Yamaha Black New Ruby Red Frost Silver	New Yamaha Black Cardinal Red

	GT80G	TT250G	MX175G	MX100G	MX80G	IT250G	IT175G	IT125G
ENGINE								
Type	2-stroke single	4-stroke S.O.H.C. single	2-stroke single	2-stroke single	2-stroke single	2-stroke single	2-stroke single	2-stroke single
Displacement	72 cc	249 cc	171 cc	97 cc	72 cc	246 cc	171 cc	123 cc
Bore and Stroke	47 x 42 mm	75 x 56.5 mm	66 x 50 mm	52 x 45.6 mm	47 x 42 mm	70 x 64 mm	66 x 50 mm	56 x 50 mm
Compression ratio	6.9 : 1	9.7 : 1	6.8 : 1	6.8 : 1	6.8 : 1	7.9 : 1	7.9 : 1	8.1 : 1
Maximum torque	4.2 ft.-lbs. (0.59 kg-m) @ 6,500 r.p.m.	15.6 ft.-lbs. (2.15 kg-m) @ 7,000 rpm	12.7 ft.-lbs. (1.76 kg-m) @ 6,500 rpm	6.3 ft.-lbs. (0.87 kg-m) @ 6,500 r.p.m.	4.00 ft.-lbs. (0.55 kg-m) @ 7,500 r.p.m.	26.0 ft.-lbs. (3.6 kg-m) @ 7,500 r.p.m.	15.9 ft.-lbs. (2.1 kg-m) @ 7,500 r.p.m.	11.5 ft.-lbs. (1.5 kg-m) @ 8,500 r.p.m.
Carburetion	(1) TK Y16P-3A	(1) Mikuni VM30SS	(1) Mikuni VM24SS	(1) Mikuni VM22SS	(1) TK Y16P-3	(1) Mikuni VM36SS	(1) Mikuni VM34SS	(1) Mikuni VM30SS
Ignition	C.D.I.	C.D.I.	C.D.I.	C.D.I.	C.D.I.	C.D.I.	C.D.I.	C.D.I.
Starting	Kick	Kick	Kick	Kick	Kick	Kick	Kick	Kick
Lubrication	Autolube	Wet sump	Autolube	Autolube	Autolube	Pre-mix	Pre-mix	Pre-mix
Transmission	4-speed	5-speed	6-speed	5-speed	4-speed	6-speed	6-speed	6-speed
CHASSIS								
Overall length	61.6" (1,565 mm)	82.3" (2,090 mm)	82.1" (2,085 mm)	70.7" (1,795 mm)	61.0" (1,550 mm)	86.8" (2,205 mm)	83.5" (2,120 mm)	82.9" (2,105 mm)
Overall width	28.0" (710 mm)	35.4" (900 mm)	33.1" (865 mm)	31.5" (800 mm)	27.2" (690 mm)	36.8" (935 mm)	36.8" (935 mm)	35.9" (900 mm)
Overall height	36.6" (930 mm)	47.4" (1,205 mm)	43.5" (1,105 mm)	37.8" (960 mm)	36.6" (930 mm)	47.4" (1,205 mm)	46.3" (1,175 mm)	44.5" (1,130 mm)
Seat height	25.8" (655 mm)	33.9" (860 mm)	31.1" (790 mm)	28.7" (730 mm)	25.4" (645 mm)	36.8" (935 mm)	35.2" (895 mm)	33.5" (850 mm)
Wheelbase	41.1" (1,045 mm)	55.1" (1,400 mm)	52.8" (1,340 mm)	46.9" (1,190 mm)	41.1" (1,045 mm)	56.3" (1,430 mm)	55.9" (1,420 mm)	53.7" (1,365 mm)
Ground clearance	6.7" (170 mm)	11.0" (280 mm)	9.8" (250 mm)	7.9" (200 mm)	7.7" (195 mm)	11.8" (300 mm)	11.4" (290 mm)	11.8" (300 mm)
Dry weight	141 lbs. (64 kg)	—	201 lbs. (91 kg)	170 lbs. (77 kg)	130 lbs. (59 kg)	240 lbs. (109 kg)	207 lbs. (94 kg)	202 lbs. (91.5 kg)
Fuel tank capacity	0.2 Imp.gals. (4.8 ℓ)	1.5 Imp.gals. (6.9 ℓ)	1.5 Imp.gals. (6.8 ℓ)	1.0 Imp.gals. (4.5 ℓ)	1.1 Imp.gals. (4.8 ℓ)	2.6 Imp.gals. (12 ℓ)	2.4 Imp.gals. (11.0 ℓ)	1.9 Imp.gals. (8.5 ℓ)
Oil capacity	0.6 Imp.qts. (0.7 ℓ)	1.4 Imp.qts. (1.6 ℓ)	0.9 Imp.qts. (1.0 ℓ)	0.9 Imp.qts. (1.0 ℓ)	0.6 Imp.qts. (0.7 ℓ)	—	—	—
Suspension								
Front	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks	Telescopic forks
Rear	Swing arm	Swing arm	Monocross suspension	Swing arm	Swing arm	Monocross suspension	Martin I Henry Monocross suspension	Monocross suspension
Brakes								
Front	Drum	Drum	Drum	Drum	Drum	Drum	Drum	Drum
Rear	Drum	Drum	Drum	Drum	Drum	Drum	Drum	Drum
Tires								
Front	2.50 x 15	3.00 x 21	2.75 x 21	2.50 x 18	2.50 x 15	3.00 x 21	3.00 x 21	3.00 x 21
Rear	2.75 x 14	5.10 x 17	3.50 x 18	3.00 x 16	2.75 x 14	5.10 x 18	4.10 x 18	4.10 x 18
Coloring	Maxim Red	Clean White	Clean White	Clean White	Clean White	Sky Blue	Sky Blue	Sky Blue

XS400SG	SR250G	RD400G	XT500G	XT250G	DT175G	DT125G	DT100G	DT50G
4-stroke S.O.H.C. twin 391 cc 69.0 x 52.4 mm 9.3 : 1 22.4 ft.-lbs. (3.1 kg-m) @ 7,500 r.p.m. (2) Mikuni BS34 Transistor Controlled Electric & Kick Wet sump 6-speed	4-stroke S.O.H.C. single 249 cc 75 x 56.5 mm 9.2 : 1 14.5 ft.-lbs. (2.0 kg-m) @ 6,500 rpm (1) Mikuni BS34 Transistor Controlled Electric Wet sump 5-speed	2-stroke twin 398 cc 64 x 62 mm 6.0 : 1 28.2 ft.-lbs. (4.0 kg-m) @ 7,000 r.p.m. (2) Mikuni VM28SS C.D.I. Kick Autolube 6-speed	4-stroke S.O.H.C. single 499 cc 87 x 84 mm 9.0 : 1 28.2 ft.-lbs. (3.9 kg-m) @ 5,500 r.p.m. (1) Mikuni VM32SS Magneto Kick Wet sump 5-speed	4-stroke S.O.H.C. single 249 cc 66 x 50 mm 9.2 : 1 14.5 ft.-lbs. (2.0 kg-m) @ 6,500 rpm (1) Mikuni VM28SS C.D.I. Kick Wet sump 5-speed	2-stroke single 171 cc 56 x 50 mm 6.8 : 1 12.7 ft.-lbs. (1.76 kg-m) @ 6,000 r.p.m. (1) Mikuni VM24SS C.D.I. Kick Autolube 6-speed	2-stroke single 123 cc 56 x 50 mm 7.2 : 1 10.0 ft.-lbs. (1.39 kg-m) @ 6,000 r.p.m. (1) Mikuni VM22SS C.D.I. Kick Autolube 6-speed	2-stroke single 97 cc 52 x 45.6 mm 7.4 : 1 6.8 ft.-lbs. (0.94 kg-m) @ 6,000 r.p.m. (1) Mikuni VM22SS Magneto Kick Autolube 5-speed	2-stroke single 49 cc 40 x 39.7 mm 6.9 : 1 2.8 ft.-lbs. (0.38 kg-m) @ 6,000 r.p.m. (1) Mikuni VM16SH Magneto Kick Autolube 5-speed
81.3" (2,065 mm) 36.6" (930 mm) 47.4" (1,205 mm) 30.3" (770 mm) 54.1" (1,375 mm) 5.3" (135 mm) 372 lbs. (169 kg) 3.1 Imp.gals. (14 ℓ) 2.5 Imp.qts. (2.6 ℓ)	79.3" (2,015 mm) 32.7" (830 mm) 44.3" (1,125 mm) 28.9" (735 mm) 52.6" (1,335 mm) 5.7" (145 mm) 271 lbs. (123 kg) 2.4 Imp.gals. (10.7 ℓ) 1.4 Imp.qts. (1.6 ℓ)	78.9" (2,005 mm) 32.7" (830 mm) 42.9" (1,090 mm) 31.3" (795 mm) 51.8" (1,315 mm) 6.1" (155 mm) 337 lbs. (153 kg) 3.6 Imp.gals. (16.5 ℓ) 1.4 Imp.qts. (1.6 ℓ)	84.4" (2,145 mm) 34.4" (875 mm) 45.7" (1,160 mm) 33.9" (860 mm) 55.7" (1,415 mm) 8.9" (225 mm) 304 lbs. (138 kg) 1.9 Imp.gals. (8.5 ℓ) 2.1 Imp.qts. (2.4 ℓ)	84.1" (2,135 mm) 35.0" (890 mm) 46.1" (1,170 mm) 33.1" (840 mm) 55.1" (1,400 mm) 9.8" (250 mm) 249 lbs. (113 kg) 1.8 Imp.gals. (8ℓ) 1.4 Imp.qts. (1.6 ℓ)	82.5" (2,095 mm) 33.5" (850 mm) 44.1" (1,120 mm) 32.5" (825 mm) 53.1" (1,350 mm) 10.4" (265 mm) 216 lbs. (98 kg) 1.5 Imp.gals. (6.8 ℓ) 0.8 Imp.qts. (0.9 ℓ)	82.1" (2,085 mm) 33.5" (850 mm) 43.3" (1,100 mm) 31.3" (795 mm) 53.0" (1,345 mm) 9.8" (250 mm) 214 lbs. (97 kg) 1.5 Imp.gals. (6.8 ℓ) 0.8 Imp.qts. (0.9 ℓ)	74.0" (1,880 mm) 31.5" (800 mm) 39.0" (990 mm) 28.7" (730 mm) 46.9" (1,190 mm) 7.9" (200 mm) 176 lbs. (80 kg) 1.0 Imp.gals. (4.5 ℓ) 0.9 Imp.qts. (1.0 e)	70.9" (1,800 mm) 30.5" (775 mm) 38.4" (975 mm) 27.8" (705 mm) 46.9" (1,190 mm) 7.9" (200 mm) 157 lbs. (71 kg) 1.1 Imp.gals. (4.7 ℓ) 1.1 Imp.qts. (1.2 ℓ)
Telescopic forks Swing arm	Telescopic forks Swing arm	Telescopic forks Swing arm	Telescopic forks Swing arm	Telescopic forks Swing arm	Telescopic forks Monocross suspension	Telescopic forks Monocross suspension	Telescopic forks Swing arm	Telescopic forks Swing arm
Hydraulic disc (1) Drum	Drum Drum	Hydraulic disc (1) Hydraulic disc (1)	Drum Drum	Drum Drum	Drum Drum	Drum Drum	Drum Drum	Drum Drum
3.00S x 18 120/90 x 16-63S Black Red Cardinal Red	3.00 x 18 120/90 x 16 New Catalina Blue	3.25S x 18 4.00 x 18 New Pearl White	3.00 x 21 3.50S x 18 New Yamaha Black	3.00 x 21 3.50 x 18 Maxim Red	2.75 x 21 3.50 x 18 Maxim Red	2.75 x 21 3.00 x 18 Crystal Silver	2.50 x 18 3.00 x 16 Maxim Red	2.50 x 18 3.00 x 16 Competition Yellow

YZ465G	YZ250G	YZ125G	YZ100G	YZ80G	YZ50G	QT50G	LC50G	YT125G
2-stroke single 465 cc 85 x 82 mm 7.0 : 1 40.8 ft.-lbs. (5.65 kg-m) @ 6,000 r.p.m. (1) Mikuni VM38SS C.D.I. Kick Pre-mix 5-speed	2-stroke single 246 cc 70 x 64 mm 8.1 : 1 27.3 ft.-lbs. (3.77 kg-m) @ 6,500 r.p.m. (1) Mikuni VM38SS C.D.I. Pre-mix 6-speed	2-stroke single 123 cc 56 x 50 mm 8.4 : 1 13.0 ft.-lbs. (1.80 kg-m) @ 9,500 r.p.m. (1) Mikuni VM32SS C.D.I. Pre-mix 6-speed	2-stroke single 98 cc 50 x 50 mm 8.4 : 1 10.1 ft.-lbs. (1.40 kg-m) @ 9,500 r.p.m. (1) Mikuni VM30SS C.D.I. Kick Pre-mix 6-speed	2-stroke single 79 cc 49 x 42 mm 8.1 : 1 7.6 ft.-lbs. (1.05 kg-m) @ 11,500 r.p.m. (1) Mikuni VM26SS C.D.I. Pre-mix 6-speed	2-stroke single 49 cc 40 x 39.7 mm 7.8 : 1 4.5 ft.-lbs. (0.62 kg-m) @ 10,000 r.p.m. (1) Mikuni VM20SH Magneto Kick Pre-mix 5-speed	2-stroke single 49 cc 40 x 39.2 mm 6.0 : 1 2.7 ft.-lbs. (0.37 kg-m) @ 4,000 rpm (1) Mikuni VM12 C.D.I. Kick Autolube Automatic/shaft drive	2-stroke single 49 cc 40 x 39.2 mm 6.0 : 1 2.9 ft.-lbs. (0.4 kg-m) @ 3,500 r.p.m. (1) Mikuni VM12SC C.D.I. Kick Autolube Automatic 2-speed	2-stroke single 123 cc 56 x 50 mm 6.4 : 1 7.2 ft.-lbs. (1.0 kg-m) @ 5,000 r.p.m. (1) Mikuni VM20SS C.D.I. Recoil Autolube 5-speed
85.6" (2,175 mm) 36.8" (935 mm) 47.0" (1,195 mm) 36.8" (935 mm) 58.3" (1,480 mm) 12.2" (310 mm) 225 lbs. (102 kg) 2.0 Imp.gals. (9.0 ℓ)	84.8" (2,155 mm) 36.6" (935 mm) 47.0" (1,195 mm) 36.8" (935 mm) 57.3" (1,455 mm) 12.2" (310 mm) 214 lbs. (97 kg) 1.7 Imp.gals. (6.5 ℓ)	83.3" (2,115 mm) 37.4" (950mm) 47.8" (1,215 mm) 37.0" (940 mm) 56.3" (1,430 mm) 13.4" (340 mm) 187 lbs. (85 kg) 1.4 Imp.gals. (6.5 ℓ)	81.1" (2,060 mm) 35.0" (890 mm) 45.9" (1,165 mm) 33.9" (860 mm) 54.1" (1,375 mm) 12.2" (310 mm) 185 lbs. (84.5 kg) 1.1 Imp.gals. (5.0 ℓ)	68.7" (1,745 mm) 30.9" (785 mm) 39.0" (990 mm) 29.1" (740 mm) 46.7" (1,185 mm) 8.9" (225 mm) 137 lbs. (62 kg) 1.0 Imp.gals. (4.7 ℓ)	59.4" (1,510 mm) 29.1" (740 mm) 33.3" (845 mm) 24.6" (625 mm) 40.4" (1,025 mm) 7.7" (195 mm) 110 lbs. (50 kg) 0.6 Imp.gals. (3.0 ℓ)	61.0" (1,550 mm) 26.0" (660 mm) 38.0" (965 mm) 27.8" (705 mm) 41.3" (1,050 mm) 4.6" (120 mm) 95 lbs. (43 kg) 0.5 Imp.gals. (2.3 ℓ) 0.7 Imp.qts. (0.8 ℓ)	60.6" (1,540 mm) 27.0" (685 mm) 38.6" (980 mm) 27.4" (695 mm) 41.3" (1,050 mm) 3.9" (100 mm) 119 lbs. (54 kg) 0.8 Imp.gals. (3.7 ℓ) 0.7 Imp.qts. (0.8 ℓ)	69.7" (1,770 mm) 39.2" (995 mm) 37.4" (950 mm) 28.1" (715 mm) 44.1" (1,120 mm) 5.1" (130 mm) 243 lbs. (110 kg) 1.5 Imp.gals. (7 ℓ) 1.1 Imp.qts. (1.3 ℓ)
Telescopic forks (Wheel travel) 300 mm Monocross Suspension (Wheel travel) 310 mm	Telescopic forks (Wheel travel) 300 mm Monocross suspension (Wheel travel) 300 mm	Telescopic forks (Wheel travel) 300 mm Monocross suspension (Wheel travel) 290 mm	Telescopic forks (Wheel travel) 200 mm Monocross suspension (Wheel travel) 200 mm	Telescopic forks (Wheel travel) 180 mm Monocross suspension (Wheel travel) 170 mm	Telescopic forks (Wheel travel) 110 mm Monocross suspension (Wheel travel) 115 mm	Telescopic forks Swing arm	Telescopic forks Swing arm	Unit swing
Drum Drum	Drum Drum	Drum Drum	Drum Drum	Drum Drum	Drum Drum	Drum Drum	Drum Drum	Disc
3.00 x 21 5.10 x 18 Competition Yellow	3.00 x 21 5.10 x 21 Competition Yellow	3.00 x 21 4.10 x 18 Competition Yellow	3.00 x 21 4.10 x 18 Competition Yellow	2.75 x 17 3.60 x 14 Competition Yellow	2.50 x 14 3.50 x 12 Competition Yellow	2.00 x 14 2.25 x 14 Sunshine Red Majolica Blue	3.50 x 10 3.50 x 10 Chappy Red Maxim Yellow	22 x 11 22 x 11 (x 2) Competition Yellow Martin I Henry

Specifications subject to change without notice.