

►The YZ 125's "work-type" inverted cartridge forks utilize larger diameter, 43mm, fork tubes to provide increased rigidity and less stiction. While new valving provides smoother, more progressive action with more consistent damping performance.



Remember to "Tread Lightly" and respect the environment. 30-day limited warranty. Warranty terms are limited. See your Yamaha dealer for details. Dress properly for your ride with a helmet, eye protection, long-sleeved shirt, long trousers, gloves and boots. Yamaha and the Motorcycle Safety Foundation encourage you to ride safely and respect the environment. For further information regarding the MSF rider course, please call 1-800-447-4700. Do not drink and drive. It is illegal and dangerous. ©1990 Yamaha Motor Corporation, U.S.A., Cypress, CA 90630



▲The new computer designed Deltabox swingarm is lightweight and more rigid. The new rear link ratio and shock absorber valving provide a more progressive ride, from the smallest stutter bumps to the largest supercross jumps.

▲New port timing, new intake & exhaust port shapes, new YPVS valve shape and timing and a new over-rev ignition feature all add up to increased mid-range to top-end engine performance. A new ratchet-type shifter provides lighter, more positive shifting.



▲The "Work-type" brakes are complete with new brake pad material designed to give you stronger stopping with better feel.

YZ125

ENGINE

Type	Liquid-cooled 2-stroke Single
Displacement	124.6cc
Bore and Stroke	56.0 x 53.7mm
Compression Ratio	9.2-10.7:1
Carburetor	Mikuni TM22SS/1
Igniter	CD
Starting	Kick
Lubrication	Premix
Transmission	6-Speed

CHASSIS

Overall Length	85.2"
Overall Width	33.5"
Overall Height	48.2"
Seat Height	37.2"
Wheelbase	57.3"
Ground Clearance	14"
Dry Weight	197 lbs
Fuel Tank Capacity	2.11 gal.

SUSPENSION

Front	Telescopic Fork
Rear	Swingarm (New Monocross)

BRAKES

Front	245mm Disc
Rear	220mm Disc

TIRES

Front	80/100-21
Rear	100/90-19

COLORING

White/Magenta