



The DT125 is a motorcycle you can take to work in the morning, and then climb the highest hill so you won't miss the sunset on the way home.


This is a motorcycle that can sail you over trails and countryside that other machines of the same displacement have

trouble getting to. The reason is Yamaha's exclusive Torque induction intake system that gives you extra power at the lower end of the rpm range. Extra power to pull through mud. Extra power to pass on the street.

The DT125 also has an extremely low noise level. This is because of a muffler that

really muffles. Becasue of rubber dampers practically everywhere. It even has a quick, quiet electric starter. And a durable motocrosstype frame.

The DT125. Take it around the block for a test ride. Then take it wherever your mind wants to go.



Pushbutton electric starter fires up the DT125's engine at the touch of a finger. Auxiliary kick starter is primary type, so you can start the engine in any gear, without hunting around for neutral.




Adjustable rear shocks can be set to the load you're carrying or the condition of the road. Yamaha's dust and water resistant brakes have traditionally set the industry standard for sure stopping




hardest jolts.




Torque Induction, Yamaha's unique intake system, utilizes a reed valve to feed the engine the exact amount of fuel and air it needs. The result is that horsepower is increased, particularly at low rpm's.



Autolube, a feature on most Yamaha two-stroke engines, automatically injects oil into the fuel mixture, eliminating the need for premixing. And, since it adjusts the flow of oil to engine load and speed, it extends engine life



Five-speed constant-mesh transmission has short throw selector for quick, smooth shifts. Yamaha gearboxes are notoriously rugged



www.legends-yamaha-enduros.com

DT125B	
PERFORMANCE	
Max. speed range	
Min. turning radius	
Min_ braking distant	Je
ENGINE	
Type	2-strake, Torque Induction, Single
Displacement	123 cc (7.51 cu. in.)
Bore & Stroke	2.205 × 1.969 In
Compression ratio	
Max. torque	10.0 ft16 @ 8,000 pm
Lubrication system	Autolube
Starting system	Electric starter & Primary
	kick starter
Ignition system	Battery
Transmission	5-speed gearbox
DIMENSIONS	み、さ、差。
Overall length	79,3 in.
	234.3 in.
Overall height	42.5Vh
Wheelbase	51 6 in
Min. ground clearar	ice
FUEL TANK	
Capacity	
OIL TANK	
Capacity	
TIRES	
Front	3.00-19-4PR
Rear	3.25-18-4PR
	ns subject to change without prior notice.
Socialino	Subject to change without prior nonce.

Someday, you'll own a Yamaha.

YAMAHA INTERNATIONAL CORPORATION 6600 Orangethorpe Ave., Buena Park, California 90620 Printed in Japan LIT-11035-05-01

