YAMAHA

YZ80/80LW



Smart technology. For smarter riders.

This is the machine you need. No question. It's the latest YZ80 from Yamaha. And for '97 we've loaded both the YZ80 and YZ80LW big wheeler with even more race-winning technology.

All new head, cylinder, pipe and CDI punch out boosted power for seriously quick acceleration off the line and out of tight turns.

An uprated gearbox makes for improved durability and slicker shifting. And with a YZ250-type front master cylinder and high friction sintered pads you've got all the brake power you need.

Yamaha YZ80 and YZ80LW. Smart technology. Smart choice.



YZ80 IKB (Ink Blue)



YZROJ W IKB (Ink Blue)



Running a re-tuned cylinder, power pipe, redesigned head and new CDI, the YZ's storming 79.4 cc liquid cooled engine kicks out even more low to mid range power for race winning acceleration out of the gate.



Handlebars Late braking helps you win-and with a new YZ250 replica front brake master

cylinder the YZ80 and

big wheel YZ80LW stop even quicker than ever! Also new for '97 are redesigned grips for improved comfort.



Footpegs

Direct spinoff from our factory racers are these new wider footrests. Featuring a larger surface area and high-grip teeth.

these lightweight pegs help reduce fatigue on rough circuits



Front brake

YZ's ultra light 2-pot caliper delivers excellent stopping power and transmits accurate rider feedback. And with

all-new high-friction sintered pads for '97, brake performance is up while wear is down!



Front/Rear suspension YZ80 and 80LW's chassis is one of the most advanced in the class. Running 36 mm upside down forks and a rising rate

Monocross rear end, these high performance motocrossers can eat up the hardest terrain and spit it out!

TECHNICAL SPECIFICATIONS

ENGINE Type

Displacement Bore and stroke Compression ratio Max. power (DIN)

Max. torque (DIN)

Lubrication Carburation Ignition Starter system Fuel tank capacity Transmission Final transmission

2-stroke, liquid-cooled single cylinder, with YPVS 46 x 47.8 mm

28.0 HP (20.6 kW)

@12.000 rpm 1.7 kg-m (16.7 Nm) @11.000 rpm

MIKUNI VM 26SS

Kick

5.0 litres 6-speed

YZ80LW

2-stroke, liquid-cooled single cylinder, with YPVS

46 x 47 8 mm

85.1

28 0 HP (20 6 kW)

@12,000 rpm

1.7 kg-m (16.7 Nm)

@11,000 rpm Premix

MIKUNI VM 26SS

5.0 litres 6-speed

CHASSIS

Overall length Overall width Overall height Seat height Wheelbase Min. ground clearance Dry weight Front suspension

Rear suspension

Front tyre Rear tyre

YZ80

1.803 mm 735 mm 1,105 mm 854 mm 1,257 mm 347 mm 66.0 kg Telescopic fork Swinging arm (Monocross) Single 220 mm ø disc Single 190 mm ø disc

70/100-17 40M

90/100-14 49M

YZ80LW

1.891 mm 735 mm 1,177 mm 890 mm 1,283 mm 389 mm 69.0 kg Telescopic fork Swinging arm (Link Suspension) Single 220 mm ø disc Single 190 mm ø disc

70/100-19 42M

90/100-16 52M

Always wear a helmet, eye protection and protective clothing. Yamaha encourage you to ride safely and respect fellow riders and the environment. Specifications and appearance of Yamaha products shown here may vary according to requirements and conditions, and are subject to change without notice. For further details, please consult your Yamaha dealer.

DEALER

Yamaha Motor (U.K.) Ltd.

Sopwith Drive The Brooklands Industrial Park Brooklands, Weybridge, Surrey KT13 OUZ Tel.:0932-35 80 00

Yamaha Motor (U.K.) Ltd



YAMAHA MOTOR FUROPE N.V. LIT-3MC-0107003-97E