



YAMAHA 175 SINGLE ENDURO

MODEL CT-1

www.legends-yamaha-enduro.com

YAMAHA 175 SINGLE ENDURO MODEL CT-1

Here's a new, exciting, ready-to-go stable mate to the ruffan-ready Enduro series. Perfectly fits in for those dirt riders who want more than the 125cc AT-1 and still aren't ready to jump on the big 250cc DT-1B. Trail riding is a breeze... the roughest terrain is soaked right up by those special Enduro front forks built for all the punishment you want to give them. And the 5-port power is almost like having an extra engine in reserve. This machine is designed from the ground up

for off the road work and back country riding or great for highway riding with big bike comfort. Special tires give dependable traction and firm footing everywhere. Primary kick starter for quick starting in any gear. Bright candy orange finish. The CT-1, with front fork reflectors on both sides, stop tail light reflectors on both sides. The stop light operates from both front and rear brakes. Meets all federal safety standards.



Available Colors: Candy Orange

www.reynoldscyclecenter.com


REYNOLDS CYCLE CENTER
2600 NORTH HIGH STREET
COLUMBUS, OHIO 43202
PH: 268-3300



The powerful 5-port engine opens up new avenues of thrilling adventure for every bike enthusiast who wants to know that he has the horsepower to start fast and get there fast.



Exclusive from Yamaha... the world-famous Autolube system has been modestly described as the greatest advance in years. Ends messy oil mix. Improves engine operation. Saves on gas.



Smooth is the word for the 5-speed transmission. Gear changes are quick and effortless. Note also that primary kick starter permits starts in any gear.



Big, wide and comfortable deep pleated seat adjusts to position of most comfort for easiest ride. Cushion stroke front forks give longer smoother service and greater shock resistance. Built to give genuine comfort on the roughest terrain.

SPECIFICATIONS OF CT-1

PERFORMANCE

Max. speed range	65 mph plus
Climbing ability	32 degrees
Min. turning radius	74.8 in.
Min. braking distance	59.3 ft. @ 31 mph

ENGINE

Type	2-stroke 5-port, Single
Displacement	171 cc (10.43 cu. in.)
Bore & Stroke	2.598 x 1.969 in. (66 x 50 mm)
Compression ratio	6.8 : 1
Max. horsepower	15.6 bhp @ 7,000 rpm
Max. torque	11.9 ft.-lb. @ 5,500 rpm
Lubrication system	Autolube
Starting system	Primary kick starter

TRANSMISSION

5-speed gearbox

DIMENSIONS

Overall length	77.4 in.
Overall width	35.8 in.
Overall height	43.1 in.
Wheelbase	50.6 in.
Min. ground clearance	9.1 in.

WEIGHT (Net)

211 lbs.

FUEL TANK CAPACITY

1.9 gal.

OIL TANK CAPACITY

1.3 qt.

TIRES

front 3.25-18-4-PR

rear 3.50-18-4-PR

Specifications subject to change without notice



YAMAHA

SINCE 1957 INTERNATIONAL CORPORATION

P.O. Box 54540, Los Angeles, California 90054 / Hawaii: Yamaha of Hawaii Inc., 1366 Dillingham Blvd., Honolulu, Hawaii 96817 / Canada: Fred Dealey Ltd., 854 West 6th Street, Vancouver 9, British Columbia, Canada.