

Full-size comfort backed up by maximum economy

 Reliable, economical 97cc two-stroke engine with Autolube oil injection system.

 Shifting is smooth, quick and easy thanks to 4-speed transmission.

 Deeply padded, extended seat ensures comfortable riding.

 Sealed drum brakes for safe, sure stops even in the rain.

 Fully enclosed drive chain reduces maintenance and eliminates grease splash.

· Light, stong square-section swing arm.

 Telescopic front forks provide smooth ride and better control.

Light rigid pressed-steel frame.

· The oil tank is located under the side cover and has an observation port to check the level.

SPECIFICATIONS

ENGINE		
Type		2-stroke, single
Bore & str	oke	
Compressi	ion ratio	6.5:1
		@8,000 rpm
Max. torpi	ue (DIN).	0.84 kg-m (8.2 Nm)
		@5,500 rpm
Lubricatio	n	Autolube
		VM20SC
		Kick
		8.61
		1.21
Assessment of the Control of the Con	The state of the s	
Final trans	smission	Chain drive
CHASSIS		
Overall ler	igth	1,915 mm
		735 mm
		1,035 mm
Wheelbase		
Dry weigh		
		Telescopic forks
		Swing arm
Brakes	(Front)	Drum
Tyres		2.50-18-4PR
		2.50-18-4 PR

www.legends=uamaha-enduros.com