

# YAMAHA Motorcycle Pocket Product Guide



[www.legends-yamaha-enduros.com](http://www.legends-yamaha-enduros.com)

## 1973

### 1973 MOTORCYCLE PRICES

RD60 – RD250 STREET MODELS

RD350 – TX500 STREET MODELS

TX650 – TX750 STREET MODELS

GT1 – GT1MX MINI ENDURO  
LT3 ENDURO

AT3 – CT3 ENDURO MODELS

D13 – R13 ENDURO MODELS

LTMX – ATMX MOTOCROSS

MX250 – MX360 MOTOCROSS

SC500 SCRAMBLER

WARRANTY POLICY

Model

Description

Price

STREET

RD60	55cc Two Stroke Single	_____
RD250	247cc Two Stroke Twin	_____
RD350	347cc Two Stroke Twin	_____
TX500	498cc Four Stroke Twin	_____
TX650	653cc Four Stroke Twin	_____
TX750	743cc Four Stroke Twin	_____

ENDURO

GT1(MX)	72cc Two Stroke Single	_____
LT3	97cc Two Stroke Single	_____
AT3	123cc Two Stroke Single	_____
CT3	171cc Two Stroke Single	_____
DT3	246cc Two Stroke Single	_____
RT3	351cc Two Stroke Single	_____



MOTOCROSS

LTMX	97cc Two Stroke Single	_____
ATMX	123cc Two Stroke Single	_____
MX250	246cc Two Stroke Single	_____
MX360	351cc Two Stroke Single	_____
SC500	496cc Two Stroke Single	_____

**OTHERS**

	_____	_____
	_____	_____
	_____	_____
	_____	_____
	_____	_____

## 100 ENDURO (LT3)

### Features

The Newest Lightweight in the Yamaha Enduro Line  
TORQUE INDUCTION With 7-port Power for GREATER  
ENGINE PERFORMANCE  
Easily Accessible Ignition  
Easy to Read Speedometer  
Enduro Front Forks  
AUTOLUBE Oil Injection  
5-speed Transmission  
Cylinder Head is Tapped for Accessory Compression  
Release  
Heavy Duty Engine Guard  
Stop Light Activated by Front or Rear Brake  
5-step Adjustable Rear Suspension  
Turn Signals Standard Equipment

### Specifications

Engine: 2-stroke, 7-port, TORQUE INDUCTION Single  
Cylinder  
Displacement: 97cc  
Speed Range: 58 mph plus  
Transmission: 5-speed, Constant-mesh  
Starting System: Primary Coupled Kick Starter  
Weight: 187 lbs.  
Climbing Ability: 27°  
Bore and Stroke: 2.047 x 1.795 in.  
Lubrication System: AUTOLUBE (a Yamaha EXCLUSIVE)  
Dimensions:  
Overall Length: 75.2 in.  
Overall Width: 35.4 in.  
Overall Height: 41.3 in.  
Wheel Base: 48.8 in.  
Min. Ground Clearance: 8.6 in.  
Fuel Tank Capacity: 1.6 US gal.  
Oil Tank Capacity: 1.3 US qt.  
Tires:  
Front: 2.75 - 18 4PR  
Rear: 3.00 - 18 4PR

**GT1 - GT1MX MINI ENDURO  
LT3 ENDURO  
AT3 - CT3 ENDURO MODELS**

**DT3 RT3 ENDURO MODELS**

## 125 ENDURO (AT3)

### Features

ELECTRIC STARTER

Enduro Styling

AUTOLUBE Oil Injection

TORQUE INDUCTION (a Yamaha EXCLUSIVE)

7-port Engine Design

5-step Adjustable Rear Suspension

5-speed Transmission

Separate Tachometer and Speedometer

Heavy Duty Skid Plate for Engine Protection

Enduro Front Forks

Polished Cases and Head

Head Tapped and Plugged for Accessory Compression Release

### Specifications

Engine: 2-stroke, 7-port, TORQUE INDUCTION Single Cylinder

Displacement: 123cc

Speed Range: 65 mph plus

Transmission: 5-speed, Constant-mesh

Starting System: Electric and Primary Coupled Kick Start

Weight: 221 lbs.

Climbing Ability: 30°

Bore and Stroke: 2.205 x 1.969 in.

Lubrication System: AUTOLUBE (a Yamaha EXCLUSIVE)

Dimensions:

Overall Length: 77.2 in.

Overall Width: 35.8 in.

Overall Height: 42.9 in.

Wheel Base: 50.6 in.

Min. Ground Clearance: 8.9 in.

Fuel Tank Capacity: 1.8 US gal.

Oil Tank Capacity: 1.3 US qt.

Tires:

Front: 3.00 - 18 4PR

Rear: 3.25 - 18 4PR

## 175 ENDURO (CT3)

### Features

NEW 7-port TORQUE INDUCTION Engine Design  
5-speed Transmission  
5-step Adjustable Rear Suspension  
Enduro Front Forks  
Dustproof and Waterproof Front and Rear Brakes  
Heavy Duty Engine Guard  
Primary Coupled Kick Starter for fast-easy starting in any gear  
AUTOLUBE Oil Injection  
Separate Tachometer and Speedometer  
Forestry Approved Spark Arrester  
Turn Signals Standard Equipment  
Game Rack Standard

### Specifications

Engine: 2-stroke, 7-port, TORQUE INDUCTION Single Cylinder  
Displacement: 171cc  
Speed Range: 67 mph plus  
Transmission: 5-speed, Constant-mesh  
Starting System: Primary Coupled Kick Starter  
Weight: 214 lbs.  
Climbing Ability: 30°  
Bore and Stroke: 2.598 x 1.969 in.  
Lubrication System: AUTOLUBE (a Yamaha EXCLUSIVE)  
Dimensions:  
    Overall Length: 78.0 in.  
    Overall Width: 35.8 in.  
    Overall Height: 43.7 in.  
Wheel Base: 50.8 in.  
Min. Ground Clearance: 9.4 in.  
Fuel Tank Capacity: 1.8 US gal.  
Oil Tank Capacity: 1.3 US qt.  
Tires:  
    Front: 3.25 - 18 4PR  
    Rear: 3.50 - 18 4PR

**AT3 - CT3 ENDURO MODELS**

**DT3 - RT3 ENDURO MODELS**

**Features**

New 72cc Reed Valve Engine

Full 4-speed Transmission

AUTOLUBE Oil Injection ends Messy Gas-Oil Mixing

Enduro Front Forks

Speedometer Standard on the GT1

Both the GT1 and GTMX have Standard Dustproof and Waterproof Brakes

Primary Coupled Kick Starter for easy-fast starting in any gear

The GTMX FOR OFF THE ROAD USE ONLY

High Front Fender on both models – Number Plate Standard on the GTMX

Heavy Duty Skid Plate for Engine Safety

**Specifications**

Engine: 2-stroke, Reed Valve, Single Cylinder

Displacement: 72cc

[www.legends-yamaha-enduros.com](http://www.legends-yamaha-enduros.com)

Transmission: 4-speed, Constant-mesh

Starting System: Primary Coupled Kick Starter

Weight: GT1: 141 lbs., GTMX: 130 lbs.

Climbing Ability: 20°

Bore and Stroke: 1.850 x 1.654 in.

Lubrication System: AUTOLUBE (a Yamaha EXCLUSIVE)

Dimensions:

Overall Length: GT1: 63.4 in., GTMX: 61.0 in.

Overall Width: 27.2 in.

Overall Height: 36.6 in.

Wheel Base: 41.1 in.

Min. Ground Capacity: 7.7 in.

Fuel Tank Capacity: 1.3 US gal.

Oil Tank Capacity: 0.7 US qt.

Tires:

Front: 2.50 – 15 4PR

Rear: 2.75 – 14 4PR



## YAMAHA MOTORCYCLE WARRANTY

As set forth herein, the term "machine" shall refer to motorcycle as manufactured by Yamaha and sold by an authorized Yamaha dealer within the United States. "Company" shall refer to Yamaha International Corporation acting through its duly authorized and franchised motorcycle dealers.

- (A) Period of warranty shall be 6 months from date of delivery or 4000 miles, whichever occurs first; 90 days for the Mini Enduro. During the period of warranty, Company guarantees to the original purchaser of each new Yamaha:
1. Any part adjudged defective by reason of faulty workmanship or material from the factory shall be performed free of charge.
  2. Any repairs and/or adjustments made necessary by faulty workmanship or material from the factory shall be replaced free of charge.
- (B) This warranty shall be effective is purchaser:
1. Submits machine to an authorized dealer for the required service checks (500, 1000, 2000, 3000 miles) as noted in the Owner's Warranty Guide Book, and
  2. Gives notice to an authorized Yamaha dealer of any and all apparent defects within ten (10) days after discovery and immediately makes the machine available for inspection and repairs at such dealer's place of business.
- (C) Warranty repairs should be performed by the selling dealer, unless the purchaser has moved more than fifty miles from the selling dealer or is touring more than fifty miles from the selling dealer.

(D) Warranty shall not extend to:

1. Machines subjected to abnormal strain or abuse.
2. Machines which have not been maintained properly or neglected.
3. Machines altered from standard condition.
4. Failures of, or failures caused by parts or accessories not manufactured by Yamaha.
5. Machines used in competition of any kind.
6. Machines designed specifically for competition, (MX, Road Racers, etc.)
7. Accident or collision damage.
8. Parts replaced due to normal wear, or routine maintenance. (Ignition components, spark plugs, etc.)
9. Machines which have had the speedometer (odometer) removed or altered.
10. Machines used for renting, leasing, or other commercial purposes.

(E) WHERE PERMITTED BY LAW:

1. COMPANY'S LIABILITY SHALL BE LIMITED TO THAT SET FORTH IN THIS WARRANTY, AND COMPANY SHALL NOT BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, INCLUDING INJURY TO PERSON OR PROPERTY.
2. COMPANY MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED; AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH EXCEED THE OBLIGATION STATED IN THIS WARRANTY ARE HEREBY DISCLAIMED BY COMPANY AND EXCLUDED FROM THIS WARRANTY.

Yamaha International Corporation  
6600 Orangethorpe Avenue  
Buena Park, California 90620