

TT125



www.legends-yamaha-enduros.com

TOUGH STUFF IN A SMALL PACKAGE

Competitive enduro riding may be one of the toughest motorcycle sports but you don't have to be a muscle-bound giant to reach the top. The Yamaha IT125 brings all the performance of its bigger brothers into the lightweight division and has the added advantage of being a compact machine that is easy to handle. The outstanding performance comes from the 123cc two-stroke single engine with Torque Induction intake which is directly based on Yamaha's GP-winning motocrossers of just a few seasons ago. The proven Monocross rear suspension gives plenty of wheel travel and toughens up under maximum compression to put up with the roughest terrains.

In addition, the IT125 has all the features you would expect on a full competition machine: aluminium skid plate, comprehensive tool kit, snain-cam chain pullers, front and rear lights, plus a speedometer.

A genuine enduro racer, the IT125 shares the aggressive styling of Yamaha's motocrossers. That aggression is reflected in its award-winning efforts in the highest levels of competition.

The lightweight wheels are shod with "rimsaver" tyres, and feature quickrelease axle nuts for extra rapid running repairs. Waterproof brakes are contained in lightweight conical hubs to reduce unsprung weight.

Superb off-road handling is guaranteed by the Monocross suspension. The rigidly-triangulated rear sub-frame is coupled to a single De Carbon-type shock absorber with tapered coil spring that permits 200mm of progressive wheel travel.

Footrests, gear lever and brake pedal are spring-loaded to fold under impact and so protect the rider's lower legs.

Although a true competition machine, the IT125 is equipped with full lighting and instrumentation—25/25W headlamp, tail lamp plus a speedometer.

The Capacitor Discharge Ignition gives a reliable spark regardless of conditions. It is maintenance-free so no worries about adjustments out on the trail.

The leading axle front forks allow 200mm of wheel travel. To keep mud and dust at bay the fork legs are protected by rubber gaiters.



www.legends-yamaha-enduros.com

IT125 SPECIFICATIONS


ENGINE

Type	2-stroke, single
Displacement	123 cc
Bore and stroke	56 x 50 mm
Lubrication	Pre-mix
Carburetion	VM30
Ignition	CDI
Starter system	Kick
Fuel tank capacity	8.5 l
Transmission	6-speed
Final transmission	Chain drive

CHASSIS

Overall length	2,115 mm
Overall width	870 mm
Overall height	1,145 mm
Seat height	860 mm
Wheelbase	1,375 mm
Ground clearance	310 mm
Dry weight	92.0 kg
Suspension	Front Telescopic forks Rear Monocross suspension
Brakes	Front Drum Rear Drum
Tyres	Front 3.00-21-4PR Rear 4.10-18-4PR

*Specifications and appearance of Yamaha motorcycles shown in this catalog may differ according to local requirements and conditions and are subject to change without notice. For further details, please consult your Yamaha dealer. Martin I Henry
Cover photo: US specifications
Always wear a helmet and eye protection.*



Valhallavägen 22:36
S-114 22 Stockholm
Tel. 08-15 80 08

