

YZ250WR

FEATURES

- · Redesigned engine uses shorter con-rod, revised porting and new expansion chamber for wider torque band and higher top-end bower.
- · Improved upside-down forks feature flex-matched inner and outer tubes for smoother action and more consistent dambing.
- · Wide ratio 5-speed transmission.
- · Monocross rear suspension uses new swinging arm and linkages for improved rear wheel tracking.
- Front brake uses a strengthened caliper and a larger 245 mm disc for improved braking performance. New front master cylinder and rear caliper feature direct-coupled hose fittings for better "feel" and easier servicing.
 - · Adjustable handlebars offer "tuned" riding position by replacing mounting brackets and upper triple clamb.
 - . The 250WR uses an 18-inch rear tyre that's more suitable for enduro riding.
 - · New expansion chamber provides 25 mm more ground clearance. oww.legends-uumaha-enduros



2-stroke, liquid-cooled, single



Monocross rear materiological

Prunt ..

Rear.

Colouring

PHORIE	
Type2-strake, b	quid-conied, sing
Dischronol	246
Bare & stroke	68.0 × 68.0 ms
Compression ratio_	88~10.6:
Lubrication	Premi
Cartoraion	T3438S
Ignitum	CD
Starter system	
Fuel tank capacity	85
Traverseen	Wide ratio 5-spect
Final transmission	Chain drive
CHASSIS	
Overall length	
Overall width	
Overall height	1,225 mm
Seat height	
Wheelese	1,480 mm
Ground character	
Dry weight	97 kg
Suspension	
Front	
Rear	Manana
Brakes	-
Prunt	
Rear.	L/tsc

80/100-21-51M

White

110/100-18-64M